

Optimum Power Services

Power, Temperature, Air – Anytime, Anywhere

OPS - AC Loadbank Nominal Specifications - at a glance

DESCRIPTION	RATING	L (mm)	W (mm)	H (mm)	W (kg)
230kW resistive only	230kw nominal rating @ 400v 3ph 50hz 240kw rated @ 415v 3ph 50hz	1320	800	1250	280
400kW resistive only	400kw nominal rating @ 400v 3ph 50Hz 431kw rated @ 415v 3ph 50hz	1364	1180	1655	600
600kW resistive only	600kw nominal rating @ 400v 3ph 50Hz 646kw rated @ 415v 3ph 50hz	2040	1540	1620	950
1000kW resistive only	1000kw nominal rating @ 400v 3ph 50Hz 1076kw rated @ 415v 3ph 50hz	2340	1540	2075	1420
2292kva resistive/reactive	2292kva nominal rating @ 400v 3ph 50Hz 2467kva rated @ 415v 3ph 50hz	3000	2440	2590	9500
5000kVA resistive/reactive	5000kva nominal rating @ 400v 3ph 50Hz 5382kva rated @ 415v 3ph 50hz	6100	2440	2590	180000

The above Load banks are all available to operate other voltages. Info on application.

Please call the sales office on 01322 381726 for a full quotation or email them at sales@optimumpowerservices.com

Office & Registered Address: Unit 4, Galley Hill Trading Estate, London Road, Swanscombe, Dartford, Kent, DA10 0AA
Tel/Fax: 01322 381726 Email: sales@optimumpowerservices.com Web: www.optimumpowerservices.com



Certificate No. FS 569808

Registered in England & Wales registration No.05970557

